

Keep In Contact

The ergonomically designed ProTalk® XLS TK-3230 is extremely comfortable to hold and operate, making it the handy choice for superior communications in retail, supermarkets, restaurants, hotels, theaters, warehousing, industrial use, facilities management, and rental fleet applications. Lightweight yet powerful, this feature-packed two-way radio promises uncompromising performance in today's demanding commercial requirements.



Retailers



Restaurants



Hotels



Warehouses



Theaters

Optional Accessories

KNB-46L

2,000mAh Li-ion Battery Pack



KSC-37

Rapid Rate Charger for KNB-46L (2.5 hours)



KMC-45

Compact Speaker Microphone



KMC-21

Lightweight Speaker Microphone



KBH-14

Spring Action Belt Clip



KHS-7

Single-muff Headset



KHS-7A

Single-muff Headset w/In-line PPT



KHS-8BL

2-wire Palm Mic w/Earphone (Black)



KHS-9BL

3-wire Palm Mic w/Earphone (Black)



KHS-22

Headset w/VOX & PTT



KHS-23

Earbud Headset



KHS-25

D-Ring Ear Hanger Headset w/Boom Microphone



KHS-26

Earbud In-line PTT Headset



KHS-27

D-Ring In-Line PTT Headset



KEP-2

Earphone Kit for KMC-17/21 (2.5 mm plug)



KMB-27

Six-unit Charger Adapter (Chargers not included)



KLH-150

Nylon Case



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details.

Specifications

- Number of channels: 6
- 64 pre-stored frequencies
- Privacy codes: 39 (QT) / 83 (DQT) code settings per radio
- 1.5W / 0.5W user switchable power output
- Power supply: 2,000mAh rechargeable Li-ion battery
- Battery life: 14 hours (saver off) / 18 hours (saver on)
- Dimensions (W x H x D): 2.07 x 4.07 x 1.13 inch (52 x 103.5 x 28.7 mm)
- Weight: 5.5 oz (155 g) with Li-ion battery
- FCC ID: ALH383200

Specifications are subject to change without notice, due to advancements in technology. ProTalk® is a registered trademark of JVC Kenwood Corporation in the United States and/or other countries. FleetSync® is a registered trademark of JVC Kenwood Corporation in the United States and/or other countries. Privacy Talk® is a registered trademark of JVC Kenwood Corporation in the United States and/or other countries.

KENWOOD

JVC KENWOOD Corporation

Communications Equipment Division

3970 Johns Creek Court, Suite 100, Suwanee, GA 90024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwoodusa.com www.kenwoodusa.com/protalkinfo



ISO9001 Registered
Communications Equipment Division
Professional Systems Business Group
JVC KENWOOD Corporation

ADS#44911 Printed in USA

KENWOOD

Portable UHF Business Two-Way Radio TK-3230



2-Year Warranty

ProTalk® XLS



Actual Size

ProTalk® XLS
Portable UHF Business Two-Way Radio
TK-3230

Only
5.5 oz



Restaurants

Retailers

Hotels

Theaters

● Compact, Lightweight Design & Operating Ease

Compact enough to carry anywhere with ease, this smart new radio has a distinctively ergonomic form that's handy to hold and operate. It weighs a mere 5.5 oz (155 g) with the rechargeable Li-ion battery and control buttons, which are simple to use with PTT, MON, MENU, CALL, UP and DOWN operations.

● 1.5 Watts Transmit Power & Range of up to 5 Miles

The ProTalk® XLS offers 1.5 watts of power to enable direct radio-to-radio communication on the same frequency (simplex) for up to 5 miles.

Talk Range	
Open areas without obstructions	Up to 5 miles (8 km)
Residential areas (near buildings)	Up to 1.5 miles (2.4 km)
In steel and/or concrete reinforced buildings	Up to 225,000 sq. ft (20,900 sq. m)
In high-rise buildings	Up to 17 floors

Note: Talk range will vary based on terrain and conditions.

● All-in-One Package

The ProTalk® XLS is ready for use immediately after purchase. It comes with all necessary accessories, including a fast charger, a 2,000 mAh Li-ion battery and a belt clip.

Battery life (5-5-90 duty cycle)	Saver on: 18 hours
	Saver off: 14 hours
Battery charging time	2.5 hours

● 64 Programmable Pre-stored Frequencies

Each of the 6 channels can be programmed by the user to any of the 64 pre-stored frequencies.

● 39-QT/ 83-DQT Coded Squelch

Sub-audible QT tone & DQT digital codes mute undesired voice traffic audio and segregate user talk groups on shared frequencies or radio system. The user can pick any of the pre-stored channel settings — 39 QT tones and 83 DQT codes.

● Compatibility

The ability to choose frequency and QT/DQT channel settings allows the ProTalk® to operate on the same channels and coded squelch tones as other UHF business radio brands. So choosing the Kenwood ProTalk® XLS will not impact on any of your previous investments in radio equipment.

● SELCALL — FleetSync® PTT ID and Caller ID Display

Kenwood's FleetSync® digital signaling system includes PTT ID digital ANI for instant radio call identification. FleetSync® also includes caller ID display and selective calling (Individual call, Group call and Broadcast call). Users can also set the alert tone (1-10, Off) for Individual call and Group/Broadcast call.

● 4-digit 7-segment LCD with Backlight

The large 4-digit 7-segment display makes it easy to check on both channel and signaling information. There is also a 3-level icon in the LCD to indicate how much battery power is left.



● Channel Scan

Scanning is a simple way to monitor multiple channels without manually searching.

● OTHER FEATURES

- Apply MIL-STD C, D, E, F - 8 items (refer to MIL-STD chart below)
- Built-in VOX • Built-in Privacy Talk® • Key Lock/Super Lock
- Compander • Battery Saver • 10-call Alert Tone • Scan
- Busy Channel Lockout



APPLICABLE MIL-STD

STANDARDS	MIL810C Method / Procedures	MIL810D Method / Procedures	MIL810E Method / Procedures	MIL810F Method / Procedures
Low Pressure	500.1 / I	500.2 / I, II	500.3 / I, II	500.4 / I, II
High Temperature	501.1 / I, II	501.2 / I, II	501.3 / I, II	501.4 / I, II
Low Temperature	502.1 / I	502.2 / I, II	502.3 / I, II	502.4 / I, II
Temperature Shock	503.1 / I	503.2 / I	503.3 / I	503.4 / I, II
Solar Radiation	505.1 / I	505.2 / I	505.3 / I	505.4 / I
Humidity	507.1 / I, II	507.2 / II, III	507.3 / II, III	507.4
Vibration	514.2 / VII, X	514.3 / I	514.4 / I	514.5 / I
Shock	516.2 / I, II, V	516.3 / I, IV	516.4 / I, IV	516.5 / I, IV